

60,000 Counts, 100kHz TRMS and CAT-III 1kV Now Over-molded Ergonomic!

AutoHold Real-Read™, BeepLit™ Continuity, BeepLit™ Diode Alert, LoZ AutoV
Hi-Lo EF Detection, VFD V & Hz, nS Measurements, T1-T2 Type-K, dBm
Crest Peaks, Speedy MaxMinAvg, Relative Zero, BeepJack™

BM780 SERIES

Professional
Multimeters



www.brymen.com



Bright People's Choice

Welectron.





BM789



BM785

789	785	FUNCTIONS & FEATURES
•	7kHz	ACV Bandwidth up to 100kHz
•		dBm Readings with Selectable Reference Impedance Values
•		AutoV LoZ Ghost-Voltage-Buster Feature; Automatic Selection of ACV and DCV
•		T1-T2 Dual Input Type-K Temperature -200.0°C to 1090°C; Selectable °F Readings
•		%4~20mA Readings to Test Process Control Loop Currents
•		nS Range 99.99nS to Extend Resistance Measurements
•	•	4-5/6 Digits 60,000 Counts Max Large Easy-to-Read LCD Display
•	•	Nominal 5/Sec Fast Measurements; Fully Auto-Ranging
•	•	31 Segment Analog Bar-graph Updates 50/Sec
•	•	Best Basic DCV Accuracy up to 0.03%+2d
•	•	Paper-White Back-Lighted LCD Display
•	•	DC+AC, AC True RMS Conversion
•	•	Intelligent Auto Power Off
•	•	Data Hold
•	•	Relative Zero Mode
•	•	Crest (Peak Hold) Captures MaxMin Changes > 0.25ms in Durations
•	•	AutoHold Real-Read™ Shows Real-time Readings to Avoid Blind Measurements
•	•	Speedy Record MaxMinAvg Readings; Updates 10/sec Nominal on DC Measurements
•	•	VFD-V & VFD-Hz Measures Fundamental V & Hz of Most Variable Frequency Drives
•	•	DC, AC, DC+AC Voltage Ranges 600.00mV to 1000.0V
•	•	DC, AC, DC+AC μ A, mA & A Ranges 600.00 μ A to 10.000A
•	•	Ohms Ranges 600.00 Ω to 60.000M Ω
•	•	Capacitance Ranges 10.00nF to 10.00mF
•	•	Line Frequency Ranges 99.999Hz to 50.000kHz
•	•	Logic Frequency Ranges 99.999Hz to 1.0000MHz
•	•	BeepLit™ Continuity Tester. Features Audible Beep & Visible Backlight Effects
•	•	BeepLit™ Diode Tester. Short-Beep-Alert and Voltage-threshold Continuity
•	•	BeepJack™ Input Warning Against Improper Plug into μ AmA/A Terminals
•	•	Rugged Fire Retarded Casing with Battery Compartment Cartridge
•	•	Over-molded Protective Holster with Probe-Holders & Tilt-Stand
•	•	Optional Purchase Magnetic Hanger Strap
•	•	HBC 1kV Fuses Protected on μ AmA/A Terminals
•	•	Transient Protection up to 8kV 1.2/50 μ s Lightning Surge
•	•	LVD Meets EN61010-1/-2-030/-2-033 to Measurement CAT III 1000V & CAT IV 600V
•	•	EMC Meets EN61326-1

Ergonomic and Handy + Professional Performance

Superb Resolution, Accuracy, Speed, Bandwidth, Safety, & Quality!

DC+AC & AC 100kHz TRUE RMS

For Non-sinusoidal & Complex Waveforms of Volts & Amps.
100kHz High Bandwidth for ACV

LINE LEVEL Hz

Measures Noisy Line Level Voltage Frequencies

INNOVATIVE BeepLit™ CONTINUITY

Quick Open-short Tests on Switches and Wires; Beep + Backlight Effects for Noisy Environments

FULLY AUTO-RANGING

Shortens the Time to Measure and Increases the Ease of Use

LOGIC LEVEL Hz AND %

Measures Digital Logic Level Frequencies and Duty Cycles

BACKLIGHTED LCD DISPLAY

For Easy Viewing in The Dark; 16 mins Auto-Off to Save Battery Power

0.03% BASIC DCV ACCURACY

Measures DCV up to 1000Vdc

REC MAX MIN AVG READINGS

Speedy Records Max, Min and Calculates Average Readings Over Time; Automatic APO Disable

dBm READINGS

Features 20 Selectable Reference Impedance Values

AutoV

Automatic Selection of ACV or DCV

LPF ACV & Hz FOR VFDs

Measures Voltage & Frequency of Most Variable Frequency Drives and Noisy Electrical Signals up to 1000Vac

LoZ GHOST-VOLTAGE-BUSTER

Low Ramp-up Input Impedance to Drain Ghost Voltages Leaving Only Hard Signal Meter Readings

BEEPJACK™ MIS-INPUT WARNING

Guards Against Improper Amps Terminals Plug-in for Voltage Measurements

RUGGED & DURABLE

Robust Enclosure; Precise & Reliable Rotary Switch; Premium Plating & Low Leakage PCB

INTELLIGENT AUTO-POWER-OFF (APO)

Stays ON While in Measurements; Intelligently Turns OFF to Extend Battery Life; Disable option

EMC

Superior Immunity to Interferences; Reliable Operations and Readings; Meets EN61326-1

ERGONOMIC & STREAMLINE BODY

Over-molded Holster Fits Nicely in One Hand; Reduced Size for Easy Carrying

RELATIVE ZERO

REL for Convenient Readings Comparison

DUAL SENSITIVITIES EF-DETECTION

Features Non-Contact (NCV) & Single-Pole Contact Voltage Detections; Selectable Hi/Lo Dual Sensitivities

LARGE 60,000 COUNTS LCD DISPLAY

5-5/6 Digits High Resolution; 5/Sec Fast Nominal Update Rate

DATA HOLD

Freezes the Displaying Reading for Later View

FAST ANALOG BAR-GRAPH

50/Sec Fast Nominal Update Rate

AUTOHOLD REAL-READ™

Shows Real-time Readings and automatically latches the last stable reading for later display

CREST MAX MIN PEAKS

Fast Captures +/- Peak Extremes at Durations as Short as 0.25ms; Automatic APO Disable

%4~20mA READINGS

Monitors and Verifies Process Control Loop Currents

TYPE-K TEMPERATURE

T1, T2 Dual Inputs; Selectable °C and °F Readings

INNOVATIVE BeepLit™ DIODE TEST

Short-Beep Alert on Forward Voltages <0.85V; Continuous Beep & Backlight Effects for Shorted Diode Continuities

CAPACITANCE

Up to 10mF for Measuring Motor Capacitors

LVD CAT III 1000V & CAT IV 600V

Certified EN61010-2-033, EN61010-1 & Relevant Standards on CAT III 1kV & CAT IV 600V

nS CONDUCTANCE

nS=1/GΩ virtually extends Resistance measurements to the order of GΩ

TRANSIENT PROTECTION

Up To 8kV 1.2/50μs Lightning Surge; Fully Certified by Independent Test Lab; Years of Credibility for Serious Users

RESISTANCE

Best Resolution 0.01Ω At 600Ω Range; 6 Auto-ranges Up To 60MΩ



ELECTRICAL SPECIFICATIONS

Accuracy is $\pm$ (% reading digits + number of digits) or otherwise specified, at 23°C $\pm$ 5°C & less than 75% relative humidity. Maximum Crest Factor <1.6:1 at full scale & < 3.2:1 at half scale, and with frequency components fall within the specified frequency bandwidth for non-sinusoidal waveforms.

DC Voltage

RANGE	Model 789	Model 785
600.00mV, 6.0000V, 60.000V	0.03% + 2d	0.03% + 2d
600.00V	0.05% + 5d	0.05% + 5d
1000.0V	0.15% + 5d	0.15% + 5d

Input Impedance: 10M Ω , 75pF nominal (280pF nominal for 600mV range)

VFD AC Voltage

RANGE	Accuracy ¹⁾
10Hz ~ 200Hz	
600.00V, 1000.0V	4% + 50d
200Hz ~ 440Hz	
600.00V, 1000.0V	1.0% + 50d ²⁾

¹⁾Signal fundamental frequency > 440Hz is unspecified

²⁾Accuracy linearly decreases from 2% + 50d @ 200Hz to 10% + 50d @ 440Hz

dBm (Model 789 only)

Range and accuracy are subject to ACmV, ACV and reference impedance selected.

Typical 600 Ω reference impedance ranges:

In ACmV: -42.22 dBm to -2.22 dBm

In ACV: -17.78 dBm to 62.22 dBm

Input Impedance: 10M Ω , 140pF nominal

Selectable reference impedance of 4, 8, 16, 32, 50, 75, 93, 110, 125, 135, 150, 200, 250, 300, 500, 600, 800, 900, 1000 and 1200 Ω

CREST mode (Instantaneous Peak Hold)

Accuracy: Specified accuracy $\pm$ 100 digits for changes > 0.35ms in duration

Availability: Voltage and Current functions

Resolution: 6000 counts

AutoHold Real-Read™

Accuracy: Specified accuracy $\pm$ 50 digits

Availability: Resistance, Continuity, LoZ AutoV, VFD Volts, Voltage and

Current functions

DC Loop Current %4~20mA (Model 789 only)

4mA = 0% (zero)

20mA = 100% (span)

Resolution: 0.01%

Accuracy: $\pm$ 25d

GENERAL SPECIFICATIONS

Display: 4-5/6 digits 60,000 counts.

Polarity: Automatic

Update Rate:

4-5/6 digits: Max 5 per second nominal

31 Segment Bar-graph: 50 per second max

Operating Temperature: -20°C to 55°C continuous operating (except on A function, see Electrical Specifications below for more details)

Relative Humidity: Maximum relative humidity 80% for temperature up to

31°C decreasing linearly to 50% relative humidity at 55°C

Pollution degree: 2

Storage Temperature: -20°C to 60°C, < 80% R.H. (with battery removed)

Altitude: Operating below 2000m

Temperature Coefficient: nominal 0.10 x (specified accuracy)/°C @ (-20°C ~

18°C or 28°C ~ 55°C), or otherwise specified

Sensing: AC and AC+DC True RMS

Safety: Double insulation per IEC/UL/EN 61010-1 Ed. 3.0, IEC/UL/EN 61010-2

-030 Ed. 1.0, IEC/UL/EN 61010-2-033 Ed. 1.0, IEC/UL/EN 61010-031 Ed. 2.0

and the corresponding CAN/CSA-C22.2 regulations to Measurement

Categories III 1000V AC & DC and Category IV 600V AC & DC

Overload Protections:

μ A & mA: 0.4A/1000V DC/AC, IR 30kA or better, F fuse

A: 11A/1000V DC/AC, IR 20kA or better, F fuse

V: 1100V DC/AC rms

mV, Ω & Others: 1000 V DC/AC rms

Transient protection: 8kV (1.2/50 μ s surge)

E.M.C.: Meets EN61326-1:2013

Power Supply: 1.5VAAA Alkaline battery x 3

Power Consumption: 10mA typical for AC & AC+DC Voltage/Current functions;

8mA typical for other functions

Low Battery: Below approx. 3.7V

APO Timing: Idle for 15 minutes

APO Consumption: 15 μ A typical

Dimension: L193mm X W89mm X H51mm

Weight: 635 gm

Accessories: Test lead pair, User's manual, Bkp60 banana plug K-type

thermocouple x 1 (Model 789 only)

Optional Accessories: BKB32 banana plug to type-K socket plug adaptor (

Model 789 only), BMH-02 magnetic hanger strap

Special Features: AutoHold; VFD; BeepLit™ Continuity; Record MAX, MIN, &

AVG readings; Crest (Instantaneous Peak hold) MAX & MIN readings; Relative

Zero mode; Data Hold, Backlight LCD display; BeepJack™ audible & visible

input warning, %420mA loop current readings (Model 789 only); T1-T2

differential temperature readings (Model 789 only); dBm readings (Model 789

only)

Welectron.

Official Distributor

www.welectron.com



BRYMEN TECHNOLOGY CORPORATION

www.brymen.com

TEL: +886 2 2226 3396 (rep)

FAX: +886 2 2225 0025

Copyright © MMXX B.T.C. All rights reserved

Specifications subject to change without notice

Patents pending. Printed in Taiwan



AC Voltage

RANGE	Model 789 ¹⁾	Model 785
Accuracy		
50Hz ~ 60Hz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	0.5% + 30d	0.5% + 30d
40Hz ~ 1kHz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	0.9% + 30d	1.2% + 30d
1kHz ~ 7kHz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	1.8% + 40d	2.0% + 40d
7kHz ~ 20kHz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	2.0% + 60d	Unspec'd
20kHz ~ 100kHz		
600.00mV ²⁾ , 6.0000V ²⁾ , 60.000V ²⁾ , 600.00V, 1000.0V	4.0% + 60d	Unspec'd

¹⁾Accuracy specified from 10% to 100% of range

²⁾Bandwidth specified to 10kHz only for 600V range

³⁾Accuracy specified from 30% to 100% of range

Input Impedance: 10M Ω , 75pF nominal (140pF nominal for 600mV range)

Residual reading less than 50 digits with test leads shorted

AC+DC Voltage

RANGE	Model 789 ¹⁾	Model 785
Accuracy		
50Hz ~ 60Hz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	0.7% + 40d	0.7% + 40d
0Hz, 40Hz ~ 1kHz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	1.2% + 40d	1.4% + 40d
1kHz ~ 7kHz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	2.0% + 50d	2.2% + 50d
7kHz ~ 20kHz		
600.00mV, 6.0000V, 60.000V, 600.00V, 1000.0V	2.5% + 70d	Unspec'd

¹⁾Accuracy specified from 10% to 100% of range

²⁾Bandwidth specified to 10kHz only for 600V range

Input Impedance: 10M Ω , 75pF nominal (140pF nominal for 600mV range)

Residual reading less than 50 digits with test leads shorted.

LoZ Auto-DCV (Model 789 only)

RANGE	Accuracy
6.0000V, 60.000V, 600.00V, 1000.0V	0.5% + 30d

LoZ Auto-DCV Threshold: > +1.0VDC or < -1.0VDC nominal
LoZ Auto-DCV Input Impedance:
Initially approx. 2.1k Ω , 140pF nominal; Impedance increases abruptly within a fraction of a second as display voltage is above 50V (typical).
Ended up impedances vs display voltages typically are:

12k Ω	@ 100V
90k Ω	@ 300V
300k Ω	@ 600V
670k Ω	@ 1000V

LoZ Auto-ACV (Model 789 only)

RANGE	Accuracy ¹⁾
50Hz ~ 60Hz	
6.0000V, 60.000V, 600.00V, 1000.0V	1.0% + 40d

¹⁾Accuracy specified from 10% to 100% of range
LoZ Auto-ACV Threshold: > 1.0VAC (50/60Hz) nominal
LoZ Auto-ACV Input Impedance:
Initially approx. 2.1k Ω , 140pF nominal; Impedance increases abruptly within a fraction of a second as display voltage is above 50V (typical).
Ended up impedances vs display voltages typically are:

12k Ω	@ 100V
90k Ω	@ 300V
300k Ω	@ 600V
670k Ω	@ 1000V

Ohms

RANGE	Accuracy ¹⁾
600.00 Ω	0.085% + 10d
6.0000k Ω , 60.000k Ω	0.085% + 4d
600.00k Ω	0.15% + 4d
6.0000M Ω ²⁾	1.5% + 5d
60.000M Ω ²⁾	2.0% + 5d
99.99M Ω ³⁾	1.0% + 10d

Open Circuit Voltage: < 1.3VDC (< 1.5VDC for 600 Ω range)

¹⁾Temperature Coefficient: 0.20 x (specified accuracy)/°C @ (-20°C ~

18°C or 28°C ~ 55°C)

²⁾Constant Test Current: 0.1 μ A Typical

³⁾Constant Test Current: 0.01 μ A Typical

⁴⁾Specified accuracy adds 0.5% @ >50M Ω

⁵⁾For Model 789 only; Specified accuracy adds 30d @ <10nS

BeepLit™ Continuity Tester

Audible threshold: between 100 Ω and 420 Ω

Response time < 100 μ s

Audible Indication: Beep Sound

Visible Response: LCD Backlight

BeepLit™ Diode Tester

RANGE	Accuracy	Test Current (Typical)	Open Circuit Voltage
3.0000V	1% + 20d	0.35mA	< 31 VDC

Short-Beep-Alert Threshold: Drop Across 0.850V
BeepLit™ continuous ON Threshold: < 0.100V
Audible Indication: Beep Sound
Visible Indication: LCD Backlight

DC Current

RANGE	Accuracy	Burden Voltage
600.00 μ A ¹⁾	0.075% + 20d	0.2mV/ μ A
6000.0 μ A	0.075% + 20d	0.2mV/ μ A
60.000mA ²⁾	0.075% + 20d	2.0mV/mA
600.00mA	0.15% + 20d	2.0mV/mA
6.0000A	0.3% + 20d	30mV/A
10.000A ³⁾	0.3% + 30d	30mV/A

¹⁾Specified with Open-circuit-voltage (OCV) of Current-loop-under-test at > 100 μ V

²⁾The meter shows a few negative residue counts when the input is short-circuited, with OCV at zero volt. It is the nature of the internal protection

circuit design, and will not affect measurement readings at nominal OCVs

greater than 100 μ V in significant measurements.

³⁾10A continuous up to ambient 40°C only, and is <3 mins on per >15 mins

off @ 40°C ~ 55°C; >10A to 20A for <30 seconds on per >15 mins off

Capacitance

RANGE	Accuracy ¹⁾
10.00nF	1.0% + 10d
100.0nF ~ 1000nF	1.0% + 2d
10.00 μ F ~ 1.000mF	1.8% + 4d
10.00mF	2.0% + 4d

¹⁾Accuracies with film capacitor or better

²⁾Temperature Coefficient: 0.20 x (specified accuracy)/°C @ (-20°C ~ 18°C or 28°C ~ 55°C)

AC Current

RANGE	Model 789 ¹⁾	Model 785	Burden Voltage
Accuracy			
40Hz ~ 3kHz			
600.00 μ A, 6000.0 μ A	0.9% + 20d	0.9% + 20d	0.2mV/ μ A
60.000mA, 600.00mA			2.0mV/mA
6.0000A, 10.000A ²⁾	1.0% + 30d	1.0% + 30d	30mV/A

¹⁾Accuracy unspecified @ <10% of range

²⁾10A continuous up to ambient 40°C only, and is <3 mins on per >15 mins

off @ 40°C ~ 55°C; >10A to 20A for <30 seconds on per >15 mins off

AC+DC Current

RANGE	Model 789 ¹⁾	Model 785	Burden Voltage
Accuracy			
0Hz, 40Hz ~ 3kHz			
600.00 μ A, 6000.0 μ A	1.0% + 30d	1.0% + 30d	0.2mV/ μ A
60.000mA, 600.00mA	1.2% + 40d	1.2% + 40d	2.0mV/mA
6.0000A, 10.000A ²⁾			30mV/A

¹⁾Accuracy unspecified @ <10% of range

²⁾10A continuous up to ambient 40°C only, and is <3 mins on per >15 mins

off @ 40°C ~ 55°C; >10A to 20A for <30 seconds on per >15 mins off

Temperature (Model 789 only)

RANGE	Accuracy ¹⁾
-200.0°C to 1090.0°C	1.0% + 1.0°C
-328.0°F to 1994.0°F	1.0% + 1.8°F

¹⁾Accuracies assume meter interior has the same temperature (isothermal

stage) of the ambient for a correct junction voltage compensation. Allow

the meter and the type-K probe set to reach isothermal stage for a

significant change of ambient temperature. It can take up to an hour for

changes > 5°C.

2)Type-K thermocouple range & accuracy not included

Hz Logic Level Frequency

RANGE	Accuracy ¹⁾
5.000Hz ~ 1.0000MHz	0.002% + 4d

¹⁾Sensitivity: >3.0Vp square wave

²⁾Specified with Pulse Width > 0.5 μ s

%Duty Cycle

5V Logic Frequency	RANGE Specified	Accuracy
5Hz ~ 1kHz	0.10% ~ 99.99%	3d/kHz+2d
1kHz ~ 10kHz	1.00% ~ 99.00%	
10kHz ~ 500kHz	20.00% ~ 80.00%	

Sensitivity: >3.0Vp