



Wide Angle USB Camera with Metal Case



5MP OV5648

(SKU: UB023301)

QUICK START GUIDE

SPECS

Camera	
Sensor	1/4" OV5648
Resolution	5MP 2592H x 1944V
Data Format	MJPEG/YUY2
Dynamic Range	67DB@8 x gain
Frame rate	MJPEG 15fps@2592 x 1944/2048 x 1536; 30fps@1080P/720P/1024 x 768/800 x 600; YUY2 5fps@720P/1080P;10fps@1024 x 768;15fps@800 x 600.
Lens	
Field of View (FOV)	H=90°
Lens Mount	M12
IR Sensitivity	Integral IR filter, visible light only
Functionality and Compatibility	
Auto Controlled Features	Contrast/ Saturation/ Exposure / White balance /Acutance
System Compatibil-	Win7/8/10, Linux, Mac and Android with UVC
Power	
Power Supply	DC 5V
Working Current	MAX 250mA
Physical	
Operating Temp.	-4°F~158°F (-20°C~+70°C)
Dimension	40x25x45mm
Connector No.	ZHR-4
Cable Length	3.3ft (1M)

INTRODUCTION

• About Arducam

Arducam has been a professional designer and manufacturer of SPI, MIPI, DVP and USB cameras since 2012. We also offer customized turnkey design and manufacturing solution services for customers who want their products to be unique.

• About this USB Camera

The UB023301 is a new member of the Arducam's USB camera family. It's a 5MP, UVC compliant, wide angle USB 2.0 camera. This USB camera is based on the 1/4" OV5648 image sensor, and you can read more about its specs in the next chapter. Arducam also provides the sample application that demonstrates some of the features of this camera.

• About UVC

The UB023301 is a UVC-compliant camera. The native UVC drivers of Windows, Linux and Mac shall be compatible with this camera so that it does not require extra drivers to be installed.

• About Customer Service

If you need our help or want to customize other models of USB cameras, feel free to contact us at support@arducam.com

QUICK START

• How to download the program

Download the APP Amcap from the following link <https://www.arducam.com/downloads/app/AMCap.exe>

NOTE:

1. For Mac OS, please open the native software facetime and select the video camera "USB Camera".
2. If used with the Android device, USB Camera APP and connect adapter are needed.

• How to connect the camera


Connect the one end of the USB cable to the connect-or provided on the back of UB023301, and connect the other end to the USB 2.0 host controller on the computer.

How to use the program (Windows demo only)

The Menu bar at the top of the shown image contains few menu items and the current preview resolution and the frame rate are displayed on the bottom bar when the application is running. The following sections describe each of the menu items in detail.


• Menu>Devices

This menu will show the available video devices to host PC. The UB023301 named "USB Camera".





• Menu>Options

The options menu can be used to select the preview and image parameters supported by this camera.





How to use the program (Windows demo only)

- Video Capture Pin



How to use the program (Windows demo only)

- Video Capture Filter -> Video Proc Amp/Camera Control



How to use the program (Windows demo only)

• Menu> Capture

The capture menu is used to capture the still image and video by using this application. You can also select the related parameters.

